

14 [Page 6, line 2, delete "to provide ^{an} additional hold down" and ^{of} insert --.] Clamp 50 provides an additional securement, holding--.

a' [Page 6, line 3, delete "of".

Page 6, line 4, delete "as" and insert --. The clamp is--.

a 2 [Page 6, line 4, delete "against" and insert --preventing the bedknife from coming loose upon--.

Page 6, line 5, after "off" insert --of the electromagnet 34--

IN THE CLAIMS

Please rewrite the following claims:

a 3 1. (Amended) A method of sharpening a front edge of bedknives adapted to be installed in a reel blade mower by means of a pivot [mounted] mount at each end, comprising the steps of:

mounting a spaced [set] pair of sets of [vertical and horizontal] locator surfaces on a fixed support rail in a bedknife grinder, each set comprised of a vertical and a horizontal surface;

a grinding both of the vertical and horizontal surfaces in each set with a single pass of the bedknife grinder wheel along a traversing path to establish parallelism and alignment with each other and the traversing path of the grinder;

positioning each bedknife to be sharpened against both sets of locator surfaces, with a rear edge against the vertical surfaces and the bottom against the horizontal surfaces so as to position the front edge away from said vertical surfaces;

energizing an electromagnet [associated] positioned with respect to each locator surface set so as to hold the bedknife